

imageRUNNER ADVANCE 525/615/715 III series

ACHIEVE HIGH PRODUCTIVITY WITH FAST, MULTIFUNCTIONAL PRINTERS




Canon uniFLOW Online
Outstanding Cloud Output Management Solution



MAIN CONFIGURATION OPTIONS

Choice of paper supply options*



*Paper supply options include up to three additional cassettes for non finisher models (i series) and up to two additional cassettes for finisher models (iZ series)

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online product configurator.

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE 525/615/715 III series

MAIN UNIT		Operating System	UFR II: Windows* 7 / 8.1 / 10 / Server 2008 / 2008 R2 / 2012 / 2012 R2 / 2016, MAC OS X (10.9 or later)
Machine type	A4 Monochrome Laser Multifunctional		PCL: Windows* 7 / 8.1 / 10 / Server 2008 / 2008 R2 / 2012 / 2012 R2 / 2016
Core functions	Print, Copy, Scan, Send and optional Fax		PS: Windows* 7 / 8.1 / 10 / Server 2008 / 2008 R2 / 2012 / 2012 R2 / 2016, MAC OS X (10.9 or later)
Processor	Canon Dual Custom Processor (Shared)		PPD: Windows* 7 / 8.1 / 10, MAC OS X (10.3.9 or later)
Control Panel	25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel		SAP Device Types are available via the SAP Market Place. Please refer to http://www.canon-europe.com/support/business-product-support for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable.
Memory	Standard: 3 GB RAM		
Hard Disk drive	250 GB		
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11b/g/n) Optional: NFC, Bluetooth Low Energy Others Standard: USB 2.0 x 2 (Host), USB 3.0 x 1 (Host), USB 2.0 x 1 (Device) Optional: Copy Control Interface	COPY SPECIFICATIONS	
		Copy Speed (ppm)* *simplex	iR ADV 525i III/525iZ III: Up to 52 (A4), Up to 80 (A5), Up to 35 (A6) iR ADV 615i III/615iZ III: Up to 61 (A4), Up to 99 (A5), Up to 35 (A6) iR ADV 715i III/715iZ III: Up to 71 (A4), Up to 113 (A5), Up to 40 (A6)
Paper Supply Capacity (A4, 80gsm)	Standard: 650 sheets 550-sheet paper cassette, 100-sheet Multi-purpose tray Maximum: 3,300 sheets (with High Capacity Cassette Feeding Unit-D1)	First-Copy-Out Time (A4)	Approx. 5 seconds or less
Paper Output Capacity (A4, 80gsm)	Standard model (iR-ADV 715i III/615i III/525i III): 500 sheets Finisher model (iR-ADV 715iZ III/615iZ III/525iZ III): 1,000 sheets	Copy resolution (dpi)	up to 600 x 600
Finishing capabilities	Standard model: Collate, Group Finisher Model: Collate, Group, Offset*, Staple *available with upper tray	Multiple Copies	Up to 9,999 copies
Supported media types	Paper Cassette: Thin, Plain, Recycled, Thick, Colour, Labels, Bond, Pre-punched Multi-purpose tray: Thin, Plain, Recycled, Thick, Colour, Transparency, Bond, Envelope	Copy Density	Automatic or Manual (9 Levels)
Supported media sizes	Paper Cassette: Standard size: A4, A5, A5R, A6, B5 Custom size: 99.0 x 148.0 mm to 215.9 x 297.0 mm Multi-purpose tray: Standard size: A4, A5, A5R, A6, B5, Envelope[No.10 (COM10), Monarch, DL, ISO-C5] Custom size: 76.2 x 127.0 mm to 215.9 x 355.6 mm	Magnification	25% - 400% (1% Increments)
Supported media weights	Paper Cassette: 60 to 135 gsm Multi-purpose tray: 60 to 199 gsm Duplex: 60 to 120 gsm	Preset Reductions	25%, 50%, 70 %
Warm-up Time	From Power On: 10 Seconds or Less* *Time from device power on, until copy ready (not print reservation) From Sleep Mode: 10 Seconds or less Quick Startup Mode: 4 seconds or less* *Time from device power on to when key operations can be performed on the touch panel display.	Preset Enlargements	141%, 200%, 400%
Dimensions (W x D x H)	Standard model: 513 x 601 x 617 mm Finisher model: 515 x 601 x 814 mm	Basic Copy Features	Preset R/E Ratios by Area, Paper Setting, Previous Setting, Favourite Setting, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel
Installation Space(W x D)	Standard model/ Finisher model: 1,052 x 823 mm (with left CRG door open + right door open + the cassette drawer open)	Special Copy Features	Two-sided Original, Finishing, Job Build, N on 1, Density Adjustment, Original Type Selection, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Job Done Notice, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed
Weight(Including toner)	Standard model: Approx. 37 kg Finisher model: Approx. 46 kg	SCAN SPECIFICATIONS	
PRINT SPECIFICATIONS		Standard type	Colour Platen and Single-pass Duplexed Automatic Document Feeder* [2-sided to 2-sided (Automatic)] * Detect Feeder Multi Sheet Feed is supported.
Print Speed (ppm)* *simplex	iR ADV 525i III/525iZ III: Up to 52 (A4), Up to 80 (A5), Up to 35 (A6) iR ADV 615i III/615iZ III: Up to 61 (A4), Up to 99 (A5), Up to 35 (A6) iR ADV 715i III/715iZ III: Up to 71 (A4), Up to 113 (A5), Up to 40 (A6)	Document Feeder Paper Capacity (80gsm)	100 Sheets
Print Resolution (dpi)	Data processing resolution: 600 x 600 (default), 1,200 x 1,200 (up to) Laser resolution: 1,200 x 600, 600 x 600	Acceptable Originals and weights	Platen: Sheet, Book, 3-Dimensional Objects (Height: up to 30 mm, Weight: up to 2kg) Document Feeder media weights: 42 to 128 gsm (BW)*, 64 to 128 gsm (CL) *A6: 52 gsm to 128 gsm (BW)
Page description languages	Standard: UFR II, PCL 6, PS 3	Supported media sizes	Platen: max. scanning size: 216.0 x 355.6 mm Document Feeder media size: A4, A5, A6, B5 , Custom size: 105.0 x 148.0 mm to 216.0 x 355.6 mm
Direct Print	Available from USB memory, Advanced space, Remote UI and Web Access* Supported file types: PDF, EPS, TIFF, JPEG, and XPS. *Only PDF print from website is supported.	Scan Speed (ipm; BW/CL, A4)	1-sided Scanning: 50 /50 (300 dpi, send) , 50/ - (600 dpi, copy) 2-sided Scanning: 100 /100 (300 dpi, send), 100/ - (600 dpi, copy)
Printing from mobile and cloud	A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information	Scan Resolution (dpi)	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2 PS fonts: 136 Roman *1 Requires optional PCL International Font Set-A1 *2 Requires optional Barcode Printing Kit-D1	Pull Scan Specifications	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows 7 / 8.1 / 10 / Server 2008 / 2008 R2 / 2012 / 2012 R2 / 2016
Print Features	Suspend Job Timeout, Profile Settings, Secured Print, Encrypted Secure Print, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Offsetting, Toner Reduction, Poster Printing, Forced Hold Printing	Scan Method	Send functionality available on all models Scan to USB Memory : Available on all models Scan to Mobile Devices and Cloud-based services: A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements. Please contact your sales representative for further information. TWAIN/WIA Pull scanning available on all models
		SEND SPECIFICATIONS	
		Destination	Standard: E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Optional: G3 FAX, IP Fax
		Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
		Send resolution (dpi)	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100
		Communication protocol	File: FTP (TCP/IP), SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE 525/615/715 III series

File Format	Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Encrypted, Device Signature), XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint, Word) Optional: PDF (Trace & Smooth, User Signature), XPS(User Signature)	Power consumption	Maximum: Approx. 1,500 W Printing: iR-ADV 715i III/715iZ III: 749.7 W ^{*1} , iR-ADV 615i III/615iZ III: 717.7 W ^{*1} , iR-ADV 525i III/525iZ III: 681.9 W ^{*1} Standby: Approx. 29.53 W ^{*1} Sleep mode: Approx. 1.0 W Plugin Off: Approx. 0.4 W ^{*2} Typical Electricity Consumption (TEC) rating ^{*3} iR-ADV 715i III/715iZ III: 3.0 kWh iR-ADV 615i III/615iZ III: 2.4 kWh iR-ADV 525i III/525iZ III: 2.0 kWh
Universal Send Features	Original Type Selection, Two-sided Original, Density Adjustment, Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages, Detect Feeder Multi Sheet Feed	Noise levels	^{*1} Reference value (measured one unit). ^{*2} Quick startup mode OFF. ^{*3} As per USA Energy Star 2.0
FAX SPECIFICATIONS			
Maximum Number of Connection Lines	1		
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps		
Compression Method	MH, MR, MMR, JBIG		
Resolution (dpi)	400 x 400, 200 x 400, 200 x 200, 200 x 100		
Sending/Recording Size	A4, A5*, A6* and B5* /A4, A5, B5 ^{*Sent as A4}		
FAX memory	Up to 30,000 pages		
Speed dials	Max. 200		
Group dials/destinations	Max. 199 dials		
Sequential broadcast	Max. 256 addresses		
Memory backup	Yes		
Fax Features	Original Type Selection, Two-sided Original, Density (for Scanning), Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed	Standards	Blue Angel
		CONSUMABLES	
		Toner Cartridges	T03 Black
		Toner Yield	Black: 51,500 pages (A4) Toner Cartridge yield in accordance with ISO/IEC 19752.
STORE SPECIFICATIONS		SOFTWARE AND PRINTER MANAGEMENT	
Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes 30,000 Maximum Pages Stored	Tracking and reporting	Universal Login Manager (ULM): Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device. uniFLOW Online Express: Combining with ULM you can gain further control and highlight expenditures per user/department and pinpoint where costs can be scaled down from a central cloud based location.
Advanced Space	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows 7 / 8.1 / 10) Concurrent Connections (Max.): SMB: 64 WebDAV: 3 (Active Sessions)	Remote management tools	iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting per service providers to offer efficient, fast and proactive maintenance) Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web based interface to each device that helps to provide remote device management and control
Advanced Space available disc space	Approx. 16GB (Standard HDD)		
Advanced Space Features	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support		
Memory Media	Standard: USB Memory		
SECURITY SPECIFICATIONS		Scanning software	Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device
Authentication	Standard: Universal Login Manager* (Device and Function Level Log-in), uniFLOW Online Express**, User Authentication, Department ID Authentication, Access Management System Optional: My Print Anywhere secure print (Requires uniFLOW) ^{* Installation, activation and registration required} ^{** No charge for this solution, however activation is required.}	Optimisation tools	Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers NetSpot Device Installer: Simple utility software that allows you to make network protocol settings for Canon devices connected to your network.
Data	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Common Criteria Certification (DIN ISO 15408) Optional: Data Loss Prevention (Requires uniFLOW)	Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services
Network	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME	Document Publishing	iW DESKTOP: Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorisation
Document	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks Optional: User signature		
ENVIRONMENTAL SPECIFICATIONS			
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity)		
Power source	220-240 V, 50/60 Hz, 4.8 A		

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE 525/615/715 III series

PAPER SUPPLY OPTIONS

Casste Feeding Unit-AR1

Paper Capacity: 550 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Thick, Colour, Labels, Bond, Pre-punched
Paper Size: A4, A5, A5R, A6, B5,
Custom size: 99.0 x 148.0 mm to 215.9 x 355.6 mm
Paper Weight: 60 to 135 gsm
Power Source: From the Main Unit
Dimensions (W x D x H): 642 x 657 x 456 mm
(attached to the main unit)
Weight: Approx. 19 kg

High Capacity Cassette Feeding Unit-D1

Upper cassette:
Paper Capacity: 550 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Thick, Colour, Labels, Bond, Pre-punched
Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 215.9 x 355.6 mm
Paper Weight: 60 to 135 gsm

Lower cassette:
Paper Capacity: 2,100 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Thick, Colour, Bond, Pre-punched
Paper Size: A4
Paper Weight: 60 to 135 gsm
Power Source: From the Main Unit
Dimensions (W x D x H): 642 x 657 x 456 mm
(attached to the main unit)
Weight: Approx. 25 kg

Cassette Module-AG1

Paper Capacity: 550 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Thick, Colour, Labels, Bond, Pre-punched
Paper Size: A4, A5, A5R, A6, B5,
Custom size: 99.0 x 148.0 mm to 215.9 x 355.6 mm
Paper Weight: 60 to 135 gsm
Power Source: From the Main Unit
Dimensions (W x D x H): 484 x 450 x 127 mm
(attached to the main unit)
Weight: Approx. 7 kg

Envelope Cassette Module-A1

Paper Capacity: 75 sheets (Envelope)
Envelope Size: COM10 (No.10), Monarch, DL, ISO-C5
Paper Weight: 80 to 100 gsm
Power Source: From the Main Unit
Dimensions (W x D x H): 484 x 450 x 127 mm
(attached to the main unit)
Weight: Approx. 7 kg

OUTPUT FEATURES

Finisher Model (IR-ADV 715IZ / 615IZ / 525IZ)

Number of Inner Trays: 2
Upper Tray Capacity*: A4, A5, B5, Custom size (148.0 x 210.0 mm to 215.9 to 355.6 mm): 400 sheets
Lower Tray Capacity*: A4, A5, B5, Custom size (148.0 x 210.0 mm to 215.9 to 355.6 mm): 100 sheets
Main unit output tray*: 500 sheets * 80 gsm
Paper Type: Thin, Plain, Recycled, Thick, Colour, Bond
Staple Paper Weight: 60 to 120 gsm
Staple Position: Corner
Staple Paper Size: A4, Custom size (210.0 x 279.4 mm to 215.9 x 355.6 mm)
Staple Capacity: 30 sheets (60 to 90 gsm), 20 sheets (91 to 120 gsm)

HARDWARE ACCESSORIES

Card Readers

MiCARDPLUS FOR ULM
Copy Card Reader-F1
Copy Card Reader Attachment-B5

SYSTEM AND CONTROLLER OPTIONS

Print Accessories

PCL International Font Set-A1
Universal Send Trace & Smooth PDF Kit-A1
Universal Send Digital User Signature Kit-C1

Send Options

Barcode Printing Kit-D1
Copy Control Interface Kit-A1
NFC Kit-C1
Connection Kit-A1 for Bluetooth LE

Barcode Printing

System Accessories

Fax Accessories

Super G3 FAX Board-AY1
Remote Fax Kit-A1
IP FAX Expansion Kit-B1

OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1

Staple Cartridge

Staple-P1

For a complete list of all hardware accessories, please refer to our website specifications page or online product configurator.

Software & Solutions



Certifications and compatibility



Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01
2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
Woodhatch
Reigate
Surrey RH2 8BF
Telephone No: 01737
220000
Facsimile No: 01737 220022
canon.co.uk

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2019